

ANY SPOT[®]

WIRELESS PERSONAL MONITOR

AS-900

The AS-900 is one of three new Wireless Personal Monitors, (WPM) for 2009 from Galaxy Audio. We have applied new technology and design for our second generation of WPMs. Wireless Personal Monitors are effective at eliminating stage noise, protecting users ears from damage, allowing the user to move around the stage or audience and continue to hear, and eliminate feedback.

The Any Spot is easy to use. The Any Spot WPM replaces floor wedges and the amplifiers that power them. Simply plug the ANY SPOT into a 'monitor out' jack on the mixing console, create the desired mix, and it's ready to deliver quality sound. The AS-900 has a single channel (fixed) UHF frequency which can transmit in either mono or stereo.

The AS-900R (receiver) features an 80mw headphone amplifier with a standard 3.5mm (1/8") headphone output. The AS-900R is sure to be plenty loud for any environment. The receiver has a built in limiter.

The AS-900T (transmitter) has two XLR/1/4" combo jack for its inputs, stereo/mono switch & headphone output w/volume control. The transmitter includes a single rack mount kit, for mounting 1 unit in one rack space. A rack tray is available for mounting two transmitters side by side in one rack space.

The 900 Band Pack Systems makes it easy for any band to Get Personal. The system includes four receivers and one transmitter. It is designed to get the whole band wireless in one package. The AS-900-4 will allow a band to send one stereo mix to 4 individuals (additional receivers may be purchased). Additional transmitters may be purchased at a later date to add mixes.

The Any Spot Series of Wireless Personal Monitors is a great alternative for performers who are tired of lugging around heavy and bulky floor monitors and tired of leaving a gig with ringing ear. The ANY SPOT allows the user to move freely around the stage or audience and continue to hear the monitor mix.



Band Pack System

AS-900-4



The 900 Band Pack Systems makes it easy for any band to Get Personal. The system Includes four receivers and one transmitter. It is designed to get the whole band wireless in one package. The AS-900-4 will allow a band to send one stereo mix to 4 individuals (additional receivers may be purchased). Additional transmitters may be purchased at a later date to add mixes.

MAKERS OF THE ORIGINAL
HOT SPOT PERSONAL MONITOR



Specifications: AS-900

System

Frequency Range and Transmitter Output Level

Band: UHF

Frequency Range: 630.2 MHz and 659.0 MHz

Transmitter Output Level: 10dBm

Operating Range Under Typical Conditions 150' (50m)

Note: actual range depends on RF signal absorption, reflection, and interference

Audio Frequency Response: +/-3dB 80Hz~16KHz

Total Harmonic Distortion: +/-30KHz deviation 1KHz tone <1%

Dynamic Range: >90dB A-weighted

Operating Temperature: Range 14°F to 122°F (-10 C° to +50 C°)

Note: battery characteristics may limit this range



Transmitter

Max Audio input level: +6dBV

Gain Adjustment Range: 40dB

Input Impedance: 100K Ω

Dimensions: 1.5" x 8.3" x 3.8" (38mm H x 212mm W x 96mm D)

Weight: 21oz. (605 g)

Power Requirements: 12-18V DC at 300mA supplied by external power supply

XLR input: Impedance balanced

Pin 1 Ground (cable shield)

Pin 2 Audio

Pin 3 No Audio



BACK VIEW AS-900

Bodypack Receiver

Audio Output Level: 80mW

Sensitivity: -94dBm for 30dB

Image Rejection: >70dB

Dimensions: 3.74" x 2.6" x 1" (95mm H x 65mm W x 25mm D)

Weight: 3.2oz (90 g) without batteries

Power Requirements: 2 (AA) size alkaline or rechargeable batteries

Battery Life: About 5 hours



TOP VIEW AS-900



MAKERS OF THE ORIGINAL
HOT SPOT PERSONAL MONITOR

Specifications subject to change without notice.

601 E. Pawnee Wichita, KS 67211 316.263.2852 FAX 316.263.0642 www.galaxyaudio.com
Distributed outside the United States by E and E Exports, Inc. 2815 Junipero Ave. Suite 101 Signal Hill, CA 92614
562.988.3447 FAX 562.989.3037
Distributed in Canada by Audio Distributors International (ADI) 1275 Newton, unit 6 Boucherville, QC J4B 5H2 Canada
450.449.8177 FAX 450.449.8180