GPS-8

GALAXY AUDIO

Full Range Personal Monitor/PA System

Included Components

- **1.** GPS-8 x1
- 2. IEC Power Cable x1
- 3. Quick Start Guide x1







Setup



Connect power cable to GPS-8, connect other end to a power outlet.




From your mixer or source, connect an XLR or 1/4" Cable into the Combo Jack Input located on the back of the GPS-8.



To loop to a second GPS-8, connect an XLR female into the output and the male end of the cable to the input of the second GPS-8.

Stand Mounting (Optional)



Loosen the knob on the back of the GPS-8 by turning counter-clockwise to ensure there is no obstruction in the mounting hole from the fastener.



Lift the GPS-8 over the speaker stand and align it up with the hole.



Bring the GPS-8 down onto the speaker stand gently until it is fit snugly.



Tighten the fastener by turning the knob clock-wise until snug.

Operation



For Line Level input, the button should be in the up position.

For Mic Level input, press the button in, the Mic On LED will light up.



Insure the input level control is turned down (fully counter-clockwise) Turn the power switch on.



Level control: turn clockwise to raise the level. Turn counter-clockwise to lower the level.



To enhance the low frequencies, press the Bass Boost button.



The green signal LED indicates you have input signal.

The Red Limiter indicates too much signal. If lit, turn the input down.



The GPS-8 is a versatile speaker which can be mounted on a speaker stand as well as be used as a wedge on stage.







Quick Start Guide



HOT SPOT PERSONAL MONITOR

BE HEARD

Other Helpful Sources

AUDIO MAKERS OF THE ORIGINAL

GPS-8 Product Page



GPS-8 Cutsheet (PDF Download) GPS-8 Manual



(PDF Download)

GPS-8 How To Video



Specifications subject to change without notice.

601 E. Pawnee Wichita, KS 67211 316. 263.2852 FAX 316.263.0642 www.galaxyaudio.com

Distributed in Canada by **Audio Distributors International** (**ADI**) 1275 Newton, unit 6 Boucherville, QC J4B 5H2 Canada 450.449.8177 FAX 450.449.8180

Printed in China V20151124

FAQ

1. Q. Can the GPS-8 be used outside of the US	Can t	he GPS-8	he used	outside	of the US
---	-------	----------	---------	---------	-----------

A. Yes, but you must change the mains switch to the proper voltage for your location.

2. Q. Can I plug a microphone directly into the GPS-8?

A. Yes, but it must be a dynamic mic. There is no Phantom Power for condenser mics.